

Housing - HC-D 7-TFL-48/O1M20S/PA BK - 1413510

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing D7, for single locking latch, Material: Polyamide, Cable outlets: 1, Lateral, Height: 48 mm, Cable gland: none, 1x M20



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Height	48 mm
--------	-------

Ambient conditions

Degree of protection	IP54 / IP65 with sealing screw
Ambient temperature (operation)	-40 °C ... 125 °C

General

Type	D7
Degree of protection	IP54 / IP65 with sealing screw
Locking type	for single locking latch
Type of the screw connection	1x M20
Pg screw connection	none
Cable exit	Lateral
Housing material	Polyamide
Ambient temperature (operation)	-40 °C ... 125 °C

Housing - HC-D 7-TFL-48/O1M20S/PA BK - 1413510

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 5.0	EC000437
----------	----------

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted

Approval details

EAC

GL

Drawings

Dimensional drawing



